

# AC Choke

This is used to improve the input power factor of the inverter power supply, reduce harmonics or suppress external surges. Install this option when the power supply capacity is 500 kVA or more and the power supply capacity is 10 times or more than that of the inverter's capacity, or when a distortion generating source such as a thyristor or a large-capacity inverter is connected to the same wiring leads.



## Specifications

### Standard Compliance

- ✓ IEC 60076
- ✓ EN 61558

### Primary/Secondary Voltage Range

- ✓ Up to 1000V

### Winding Material

- ✓ Aluminium Foil
- ✓ Copper Foil
- ✓ Enameled/Nomex insulation Aluminium Wire
- ✓ Enameled/Nomex insulation Copper Wire

### Silicon Steel

- ✓ Non Grained Oriented Silicon Steel (NGO)
- ✓ Grained Oriented Silicon Steel (GO)

### Varnish

- ✓ High grade polyester varnish

### Insulation Class

- ✓ Based on IEC 60085 Insulation Thermal Class
- ✓ Class Y (90°)
- ✓ Class A (105°)
- ✓ Class E (120°)
- ✓ Class B (130°)
- ✓ Class F (155°)
- ✓ Class H (180°)
- ✓ Class N (200°)

### Cooling

- ✓ Air Natural Cooling (AN)
- ✓ Air Force Cooling (AF)

### Ambient Temperature

- ✓ Maximum ambient temperature 40°C
- ✓ Up on customer request

### Metal Enclosure Protection Class

- ✓ Standard enclosure IP20
- ✓ Up to enclosure IP43

### Certifications

- ✓ CE

### Capacity

- ✓ Up to 2000KVA



## Product Enquiry

### Contact:

Email : [sales@tamura.com.my](mailto:sales@tamura.com.my)

Telephone : +6 03 5525 6000

Fax No : +6 03 5510 1013

[Send Enquiry](#)

## Catalog

[Download PDF](#)



## CONTACT US

Tamura Electronics (M) Sdn. Bhd. (17297-M),  
 Lot No.2, Jalan Halba 16/16, Seksyen 16,  
 40200 Shah Alam,  
 Selangor, Malaysia.

Telephone : 603-5525 6000  
 Fax : 603-5510 1013  
 E-Mail : [sales@tamura.com.my](mailto:sales@tamura.com.my)